SPECIFICATION SUBMITTAL SHEET


jones stephens corporation


LOG LIGHTER VALVES
WITH T-BURNERS




features and benefits:

- Solid brass escutcheon, 1/4" key and close nipple orifice included
- Individually tested (pressure test open and closed after installation)
- Angle: 188,000 BTU / Straight: 120,000







PART NO.	DESCRIPTION	Α	В	С	D	E	
□ L75-406	CP angle natural gas	12 ¹ /4"	1 ¹ /4"	1 ¹ /2"	2 ¹ /4"	23/4"	
□ L75-407	PB angle natural gas	12 ¹ /4"	1 1/4"	1 ¹ /2"	2 1/4"	23/4"	
□ L75-408	CP straight natural gas	12 ¹ /4"	1 ¹ /4"	1 1/2"	2 1/4"	-	
□ L75-409	PB straight natural gas	12 ¹ /4"	1 ¹ /4"	1 1/2"	2 1/4"	23/4"	
☐ L75-400	CP angle LPG	12 ¹ /4"	1 ¹ /4"	1 1/2"	2 1/4"	4"	
□ L75-401	PB angle LPG	12 ¹ /4"	1 ¹ /4"	1 1/2"	2 1/4"	23/4"	
☐ L75-402	CP straight LPG	12 ¹ /4"	1 ¹ /4"	1 1/2"	2 1/4"	23/4"	
☐ L75-403	PB straight LPG	12 ¹ /4"	1 ¹ /4"	1 1/2"	2 1/4"	23/4"	

PART NO.	F	G	н	1	J	K	L
□ L75-406	1 ¹ /4"	2″	3 3/4"	3″	1/2"	-	-
□ L75-407	1 ¹ /4"	2″	3 3/4"	3″	1/2"	-	-
□ L75-408	1 ¹ /4"	2″	3 3/4"	3″	1/2"	4"	2 1/2"
□ L75-409	1 ¹ /4"	2″	3 3/4"	3″	1/2"	3 3/4"	2 ⁵ /8"
□ L75-400	1 ¹ /4"	2"	3 3/4"	3″	1/2"	-	-
□ L75-401	1 ¹ /4"	2"	3 3/4"	3″	1/2"	-	-
□ L75-402	1 ¹ /4"	2″	3 3/4"	3″	1/2"	4"	2 ⁵ /8"
□ L75-403	1 ¹ /4"	2″	3 3/4"	3″	1/2"	4"	2 ⁵ /8"
1							