Swirl-way® Rectangular Whirlpool or Bathtub



Bathtub and Whirlpool Features _

- 60" x 32" x 21-1/2" rectangular bathtub
- Sculpted armrests and lumbar backrest
- One pillow
- Available in left and right hand drain configurations
- Integral tile flange and apron with removable access panel
- Mansfield® Limited Ten Year Warranty
- Available in standard colors (white, almond, biscuit and bone) and premium colors (British khaki, sterling silver, black and ice gray)

Basic Whirlpool Features

- Four back jets 2 directional and 2 rotational, plus 2 directional foot jets and 4 adjustable body jets.
- Single speed pump
- 1-button electronic keypad
- · Color match trim
- Dual air controls

Luxury Whirlpool Features

- Four back jets 2 directional and 2 rotational, plus 2 directional foot jets and 4 adjustable body jets.
- Variable speed pump
- 5-button electronic keypad with digital temperature readout
- Metal trim upgrades
- Chromotherapy system
- In-line heater



Model 5024LUX

Options _

Cable Drain

Lift and Turn Drain

Model #	Description		Model #	Description	
SW1319	Standard Colors		PF1320	Polished Chrome	PLANCE.
SW1320	Polished Chrome		PF1321	Everbrass (PVD)	
SW1321	Everbrass (PVD)		PF1322	Brushed Nickel	
SW1322	Brushed Nickel		PF1323	Oil Rubbed Bronze	
SW1323	Oil Rubbed Bronze	•	SWA100	Rainbow Pillow	

Whirlpool Options _____

Metal Trim

Model #	Description		Model #	Description	
SW1335	Chrome				
SW1336	Everbrass (PVD)	900	SWP151	In-line water heater	
SW1337	Brushed Nickel				
SW1338	Oil Rubbed Bronze				







Specifications

Model #	Description	Codes/Standards
5524L	60" X 32" X 21-1/2" Rectangular Bathtub - Left Hand	
5524R	60" X 32" X 21-1/2" Rectangular Bathtub - Right Hand	
5024LBAS	60" X 32" X 21-1/2" Basic Whirlpool Package - Left Hand	UPC USPC US
5024RBAS	60" X 32" X 21-1/2" Basic Whirlpool Package - Right Hand	® Intertek
5024LLUX	60" X 32" X 21-1/2" Luxury Whirlpool Package - Left Hand	
5024RLUX	60" X 32" X 21-1/2" Luxury Whirlpool Package - Right Hand	


Specification	Description	Specification	Description
Material	Acrylic, fiberglass reinforced	Number of Jets	10
Construction	Self-contained, pre-plumbed whirlpool bath, mounted on a pre-leveled base	Water Capacity	27 gal. (min.) / 57 gal. (max.)
Pump Motor	Basic: 1.5 HP Single speed induction pump Luxury: 1.5 HP Variable speed induction pump	Floor Loading Weight	47 lbs. / sq. ft. (229 kg/m ²)
Electrical Requirements	Basic: One 120V, 20 Amp, GFCI dedicated circuit. Optional heater: separate 120V, 20 Amp, GFCI dedicated circuit. Luxury: Two separate 120V, 20 Amp, GFCI dedicated circuits.	Shipping Weight	whirlpool - 160 lbs. bathtub - 125 lbs.
On/Off Control	Basic: 1-button electronic control pad Luxury: 5-button electronic control pad with digital readout showing temperature of water, speed of pump and time remaining in 20-minute cycle.	Warranty	Limited Ten Year


Technical Information _





Units available Right or Left Hand Drain (Left Hand Shown)





NOTE; Rough-In measurements may vary +/- ¼" Note: Install this product according to the installation guide.

These dimensions are nominal and subject to change without notice.

When tested for compliance to the requirements of ASME A112.19.7M for "Whirlpool Bath Appliances" and ANSI Z124.1.2M "American National Standard for Plastic Bathtub and Shower Units", the tested units are found to comply and are acceptable for listing under IAPMO R & T.

Certified for permanent electrical connection only.

