


Type
Project
Catalog No.
Lamp/Wattage

NL-3318

Adjustable Eyeball with Baffle

TRIM DIMENSIONS



Trim OD: 3-5/8"
Height: 2"

FEATURES

Trim

Metal trim with adjustable eyeball can be rotated 358° horizontally and 10° vertically. Precision spun 0.040 aluminum baffle with deep grooves to reduce aperture glare. Gimbal ring allows lamp to be mounted on top of the trim. Separate trim ring available in metal, may also be used with custom combination of ring finishes.

Mounting

Trim includes three trim clips that securely mount trim in housing.

Compatible Housings

Compatible with Line Voltage and Low Voltage housings. See individual specification sheets for more information.

Lamp

Line Voltage

50W 120V MR16 GU10 Max. (NH-350AT; NHIC-350AT; NHR-354AT)

Low Voltage

IMPORTANT: DO NOT USE GLASS LENS (PROVIDED) WHEN ALREADY USING LAMP WITH GLASS COVER
20W-50W 12V MR16 (NL-301 Series; NLIC-301 Series; NLR-304 Series)

Labels and Listings

cULus Listed for Damp Location when used with compatible housing.

Compatible Housings

LINE VOLTAGE			
Item Number	Installation Type	Lamp	Dimensions
NH-350AT	Non-IC Air-Tight New Const.	50W MR16	W: 6-3/8" L: 16" H: 5-5/8"
NHIC-350AT	IC Air-Tight New Construction	50W MR16	W: 6-3/8" L: 16" H: 8-1/8"
NHR-354AT	Non-IC Air-Tight Remodel	50W MR16	W: 4-1/4" L: 11-1/4" H: 5-5/8"
LOW VOLTAGE			
NL-301QAT/20	Non-IC AT New Const., Mag.	20W MR16	W: 6-3/8" L: 16" H: 5-5/8"
NL-301QAT/37	Non-IC AT New Const., Mag.	37W MR16	W: 6-3/8" L: 16" H: 5-5/8"
NL-301QAT	Non-IC AT New Const., Mag.	50W MR16	W: 6-3/8" L: 16" H: 5-5/8"
NL-301AT/1EL	Non-IC AT New Const., Elec.	50W MR16	W: 6-3/8" L: 16" H: 5-5/8"
NLIC-301QAT/20	IC Air-Tight New Const., Mag.	20W MR16	W: 6-3/8" L: 16" H: 8-1/8"
NLIC-301QAT/37	IC Air-Tight New Const., Mag.	37W MR16	W: 6-3/8" L: 16" H: 8-1/8"
NLIC-301QAT	IC Air-Tight New Const., Mag.	50W MR16	W: 6-3/8" L: 16" H: 8-1/8"
NLIC-301AT/1EL	IC Air-Tight New Const., Elec.	50W MR16	W: 6-3/8" L: 16" H: 8-1/8"
NLR-304QAT/20	Non-IC Air-Tight Remodel, Mag.	20W MR16	W: 4-1/4" L: 11-1/4" H: 5-5/8"
NLR-304QAT/37	Non-IC Air-Tight Remodel, Mag.	37W MR16	W: 4-1/4" L: 11-1/4" H: 5-5/8"
NLR-304QAT	Non-IC Air-Tight Remodel, Mag.	50W MR16	W: 4-1/4" L: 11-1/4" H: 5-5/8"
NLR-304AT/1EL	Non-IC Air-Tight Remodel, Elec.	50W MR16	W: 4-1/4" L: 11-1/4" H: 5-5/8"

Adjustable Eyeball with Baffle

- NL-3318B: Black Adjustable Eyeball with Black Baffle and Black Metal Ring
- NL-3318BZ: Bronze Adjustable Eyeball with Bronze Baffle and Bronze Metal Ring
- NL-3318C: Chrome Adjustable Eyeball with Black Baffle and Chrome Metal Ring
- NL-3318CO: Copper Adjustable Eyeball with Copper Baffle and Copper Metal Ring
- NL-3318G: Gold Adjustable Eyeball with Black Baffle and Gold Metal Ring
- NL-3318N: Natural Metal Adjustable Eyeball with Natural Metal Baffle and Natural Metal Ring
- NL-3318W: White Adjustable Eyeball with White Baffle and White Metal Ring