

NS-42 / NS-43 / NS-44 / NS-46 / NS-52 / NS-53

4" Reflector with Ring

Type

Project

Catalog No.

Notes

FEATURES

Trim: Precision spun 0.050 aluminum high grade reflector. Separate trim ring available in metal, may also be used with custom combination of plastic or metal ring finishes.

Mounting: Trim includes three trim clips that securely mount trim in housing.

COMPATIBLE HOUSINGS

Compatible with line voltage and GU24 housings. See individual specification sheets for more information.

LAMP

GU24:

· 15W R30 GU24 (NHIC-4G24AT; NHRIC-4G24AT)

Line Voltage:

· 50W R20/PAR20 Maximum (NFBIC-4INCATA ; NSIC-4010AT; NS-4010AT; NSR-4040AT; NSRIC-4040AT)

LABELS AND LISTINGS

cULus Listed for Damp Location when used with compatible housing.



PRODUCT IMAGES AND DIMENSIONS



NS-44HZ



NS-42G



NS-42B



NS-43BZ



NS-44




NS-52



NS-53



NS-53BZ



4" Reflector with Ring

Catalog No.

- NS-42G = 4" Specular Gold Reflector with Gold Metal Ring
- NS-43B = 4" Specular Black Reflector with Black Metal Ring
- NS-43BZ = 4" Specular Black Reflector with Bronze Metal Ring
- NS-44 = 4" Specular Clear Reflector with White Metal Ring
- NS-44HZ = 4" Haze Reflector with White Metal Ring
- NS-46 = 4" Specular White Reflector with White Metal Ring
- NS-52 = 4" Natural Metal Reflector with Natural Metal Ring
- NS-53 = 4" Copper Reflector with Copper Metal Ring
- NS-53BZ = 4" Bronze Reflector with Bronze Metal Ring

Compatible Housings

Catalog No.

- NFBIC-4INCATA = 2-Hour Fire Rated New Construction / 50W max.
- NSIC-4010AT = IC Air-Tight Double Wall New Construction / 50W max.
- NS-4010AT = Non-IC Air-Tight Double Wall New Construction / 50W max.
- NSRIC-4040AT = IC Air-Tight Remodel / 50W max.
- NSR-4040AT = Non-IC Air-Tight Remodel / 50W max.
- NHIC-4G24AT = ICAT GU24 New Construction, 15W Max
- NHRIC-4G24AT = ICAT GU24 Remodel, 15W Max

Example: NS-44HZ = 4" Haze Reflector with White Metal Ring