

SPECIFICATION SHEET



TWO HANDLE LAVATORY FAUCET



Model #: _____

Specific Features: _____

Project Name: _____

Submitted For: _____

Date: _____

- Lever Handles
- J Style Rigid Spout
- 4-1/16" Reach, 3-11/16" From Deck to Aerator
- Ceramic Disc Cartridges
- 3-Hole 4" Installation
- 50/50 Pop-Up Drain Assembly
- With 1.2 GPM Flow Rate

L-7570 SHOWN **ADA**

Model #	Features	Finish	
L-7570*		CP	
L-7570-BN*		PVD BN	
L-7570-ORB*		ORB	
L-7570B*	Builder Tract Pack	CP	
L-7570B-BN*	Builder Tract Pack	PVD BN	

Olympia products are engineered and manufactured to meet the following standards and codes:

- ASME A112.18.1
- ANSI A117.1
- ANSI / NSF 61, SECTION 9
- CONTAINS NO MORE THAN 0.25% WEIGHTED AVERAGE LEAD CONTENT

* Aerator limited to 1.2 GPM Flow Rate
 * E0.5 - 0.5 GPM Flow Rate Aerator Available upon request

Note:
 Optional 1" Shank
 Extension (OP-490051)
 Available.

